

Replacement windows

1) Number to be installed _____

2) Will the size of any window or door openings be changed?

Yes No

If yes, drawings must be provided showing structural alterations to accommodate reduced or increased opening sizes. Show headers or lintels as applicable.

Window or door sizes that exceed requirements for new construction may not be reduced below new construction requirements. Window or door sizes less than that required for new construction may not be further reduced. Windows required for emergency egress from residential sleeping rooms may not be eliminated or altered in such a manner as to be rendered unsuitable for this purpose.

3) U-factor of replacement windows _____

4) Glazing in hazardous locations

Does the project involve new glazing (glass) in any of the following locations?

a) Within 24" of a door and less than 60" above the floor Yes No

b) Individual pane greater than 9 sq. ft., bottom edge less than 18" above floor, top edge more than 36" above floor, walking surface within 36" horizontally of glazing. Yes No

c) Enclosures for or walls facing hot tubs, whirlpools, saunas, steam rooms, bathtubs and showers or in any portion of a building wall enclosing these compartments where the bottom exposed edge of the glazing is less than 60 inches above a standing surface. Yes No

d) Walls enclosing stairway landings or within 60 inches of the top and bottom of stairways where the bottom edge of the glass is less than 60 inches above the walking surface. Yes No

5) Required fall prevention devices

Is the lowest part of the clear opening of any window within twenty-four inches (24") of the finished floor AND more that seventy-two inches (72") above the finished grade or surface below? Yes No